

Certificate No:

MED-B-9499

Item No:

A.1/3.16

Job Id:

344.1-004293-2

EC TYPE EXAMINATION CERTIFICATE

Application of: Council Directive 96/98/EC of 20 December 1996 on Marine Equipment as amended by directive 2012/32/EU, issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Directorate. This Certificate is issued by DNV GL under the authority of the Government of the Kingdom of Norway.

This is to certify:

That the Fire Doors

with type designation(s)

MANTA B-15 Single Leaf Door Cabin



Issued to

**Manta Sezana, Proizvodnja in trgovina d.o.o.
Sežana, Slovenia**

is found to comply with the requirements in the following Regulations/Standards:

**Annex A.1, item No. A.1/3.16 and Annex B, Module B in the Directive. SOLAS 74 as amended,
Regulation II-2/and IMO FTP Code**

Further details of the equipment and conditions for certification are given overleaf.

**Høvik, 2014-11-20
for DNV GL**This Certificate is valid until
2019-04-23
**Marianne Strand Valderhaug
Head of Department**Notified Body No.: **0575**DNV GL local office:
Rijeka
**Rolf Emilsen
Surveyor**

The Certificate is subject to terms and conditions overleaf. Any significant changes in design or construction of the product, or amendments to the Directive or Standards referenced above may render this Certificate invalid. The product liability rests with the manufacturer or his representative in accordance with Council Directive 96/98/EC, as amended. The Mark of Conformity may only be affixed to the product and a Declaration of Conformity may only be issued when the production/product assessment module referred to in the council directive, is fully complied with.

Certificate No: **MED-B-9499**
Item No: **A.1/3.16**
Job Id: **344.1-004293-2**

Product description

"MANTA B-15 Single Leaf Door Cabin"

a 61 mm thick single leaf hinged door with door leaf constructed of an insulating core of three 19 mm layers mineral wool "KNAUF MHTB 700" of density 150 kg/m³, manufacturer by Knauf Insulation, Slovenia, faced on both sides with 0.8 mm thick steel sheets. Between the two insulation plates is a 2 mm acoustic insulation material "Promasound TL" of density approx 2100 kg/m³. The insulation is fastened to the door leaf with adhesive.

The door may be fitted with two ventilation grills, upper and lower, 490 mm x 130 mm (W X H), and with an open inside space 450 mm x 19 mm, between the two ventilation grills.

The opening between the door leaf and door frame were sealed with two profiled gaskets and one intumescent strip.

The door frame is made from 1.5 mm steel sheet and is bolted, M6 x 16 mm screws or steel bolts 4.8 x 35 mm both with 388 mm spacing. The door frame may also be welded to the panel. The door leaf is fixed to the door frame with three hinges.

For further details, see the drawings in the test reports listed under Type Examination documentation below.

Application/Limitation

The door is approved for use as an integrated part of fire retarding division of class B-15.

Restricted application: Fire against the door side with upper mounted ventilation grille.

Note that this is a fire safety certificate which only covers fire technical properties (i.e. not to cover strength evaluations related to watertightness, weathertightness, etc.).

Maximum door leaf size: 1163 mm x 2142 mm (W x H).

Maximum clear door opening: 1100 mm x 2100 mm (W x H).

The door has been successfully tested with extended test period in compliance with IMO MSC.1/Circ. 1319.

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each door is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test Report Nos. P 0934/13-530-5, dated 21 February 2014, from ZAG Fire laboratory and Fire Engineering, Slovenia.

Assessment No. 530/HM-DN 0934/13-7 dated 3 October 2014 from ZAG Fire laboratory and Fire Engineering, Slovenia (Alternative frame fixing arrangement with steel bolts).

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product is to be marked with name of manufacturer, type designation, fire technical rating, the MED Mark of Conformity, and USCG approval number if applicable (see below and page 3).



Certificate No: **MED-B-9499**
Item No: **A.1/3.16**
Job Id: **344.1-004293-2**

Mark of Conformity

The manufacturer is allowed to affix the Mark of Conformity according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and shall issue a Declaration of Conformity, only when the module D or E or F of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

Module E: The quality system for inspection and testing shall be approved by the Notified Body.

Module F: Compliance of the products to type as described in this EC Type-Examination Certificate must be verified by the Notified Body who also shall issue a Certificate of Conformity.

USCG Approval

An U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005.

